




Type: 38-pin, 0.50 mm pin pitch TSSOP




Package Drawing

Designator: LE Type: 8-pin, 0.65 mm pin pitch TSSOP







N = Last 3 digits of device part number \mathcal{A} = Supplier emblem

Y = Last two digits of year of manufacture

W = Week of manufacture

Branding scale and appearance at supplier discretion

For Reference Only; not for tooling use (reference MO-153 AA)

Dimensions in millimeters

Dimensions exclusive of mold flash, gate burrs, and dambar protrusions Exact case and lead configuration at supplier discretion within limits shown

A Terminal #1 mark area


Branding scale and appearance at supplier discretion

Copyright ©2008-2013, Allegro MicroSystems, LLC drawings are for reference only; not for tooling use. Refer to the individual datasheet for information on a specific product package. Allegro MicroSystems, LLC drawings are for reference only; not for tooling use. Refer to the individual datasheet for information on a specific product package. Allegro MicroSystems, LLC drawings are for reference only; not for tooling use. the right to make, from time to time, such departures from the detail specifications as may be required to permit improvements in the performance, reliability, or manufacturability of its products. Before placing an order, the user is cautioned to verify that the information being relied upon is current. The information included herein is believed to be accurate and reliable. However, Allegro MicroSystems, LLC assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.

Package Drawing


Designator: LE

Type: 20-pin, 0.65 mm pin pitch TSSOP






Type: 38-pin, 0.50 mm pin pitch TSSOP with internally fused pins for thermal dissipation



Internal configuration of fused pins is device-dependent




Type: 16-pin, 0.65 mm pin pitch TSSOP with exposed thermal pad






Type: 20-pin, 0.65 mm pin pitch TSSOP with exposed thermal pad





Type: 24-pin, 0.65 mm pin pitch TSSOP with exposed thermal pad





Type: 28-pin, 0.65 mm pin pitch TSSOP with exposed thermal pad

