A3211 and A3212

MICROPOWER, ULTRA-SENSITIVE HALL-EFFECT SWITCHES

Datasheet Addendum


This addendum details the packing specifications for the EL package $(2 \text{ mm} \times 2 \text{ mm} \text{ footprint})$ to the information offered in the main datasheet for these devices.

For parameters not listed in this addendum, refer to the main datasheet for these devices. In the event of a conflict between this addendum and the main datasheet, this addendum takes precedence.



A3211 and A3212 MICROPOWER, ULTRA-SENSITIVE HALL-EFFECT SWITCH

EL Package (2 mm × 2 mm footprint), LT Packing Instruction (embossed tape and reel)




- Round Sprocket Holes Cover Tape Pin #1 Mark
 Reel Label Carrier Tape
- 1. Pocket may have interior pedestals within specifications, at supplier discretion
- 2. Pocket centerlines to cavity center, not to pocket inspection hole
- 3. A₀ and B₀ measured 0.3 mm above exterior bottom of pocket
- 4. Pocket dimensions defined with reference to ANSI/EIA 481

Pin #1 oriented in quadrant 1 (ref. ANSI/EIA 481) (trailing edge of device, as unreeled, side nearest round sprocket holes)

Tape Dimensions

Package Designation-	Carrier Tape (mm)			Cover Tape
Instruction	Tape Lengths	Sprocket Holes	Pocket Cavity	(mm)
EL-LT: 7-in. reel,	W: 12.0 ±0.3	D ₀ : 1.5 +0.1/–0.0	A ₀ : 2.40 ±0.1	
3000 pieces/reel	E ₁ : 1.75 ±0.1	P ₀ : 4.0 ±0.1	B ₀ : 2.40 ±0.1	W _C : 9.2 ±0.1
75-80 leader pockets*	F: 5.5 ±0.05	P ₁ : 4.0 ±0.05	K ₀ : 0.80 ±0.1	T ₁ : 0.0022 ±0.022
40-50 trailer pockets	T: 0.30 ±0.05	P ₂ : 2.0 ±0.05	D ₁ : 1.0 min.	

Leader pockets are the first off the reel when the tape is unreeled for dispensing devices. Trailer pockets are the last pockets off the reel when unreeled for dispensing devices.



Reel Width, millimeters [inches]

Tape Width	Reel Type	W ₁ (inside, at Hub)	W ₂ (outside, at Hub), Max.
12 [.472]	7 in.	12.4 +2.0/–0.0 [.488 +.079/–.000]	18.4 [.724]

Reel Common Dimensions, millimeters [inches]

Reel Type	Α	N	В	С	D
7 in.	180.0 ±0.50	50.0 ±0.50	1.5 Min.	13.0 +0.5/–0.2	20.2 ± 0.500
	[7.00]	[1.969 ±.020]	[.059]	[.512 +.020/–.008]	[.795 ±.020]



A3211 and A3212 MICROPOWER, ULTRA-SENSITIVE HALL-EFFECT SWITCH

Revision History

Number	Date	Description
1	July 10, 2020	Minor editorial updates

Copyright 2020, Allegro MicroSystems.

Allegro MicroSystems reserves the right to make, from time to time, such departures from the detail specifications as may be required to permit improvements in the performance, reliability, or manufacturability of its products. Before placing an order, the user is cautioned to verify that the information being relied upon is current.

Allegro's products are not to be used in any devices or systems, including but not limited to life support devices or systems, in which a failure of Allegro's product can reasonably be expected to cause bodily harm.

The information included herein is believed to be accurate and reliable. However, Allegro MicroSystems assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.

Copies of this document are considered uncontrolled documents.

